

CHAMPION



420
With
Hook



421
With
Shackle



406
Tail
Board

- Hooks and side plates are forged alloy steel and heat treated.
- Shackles and yokes are forged and heat treated steel.
- All parts are forged.
- Side plates are designed to eliminate possibility of rope jamming.
- Can be furnished with bronze bushings or sealed roller bearings.
- Opening feature permits insertion of rope while block is suspended from gin-pole.
- Can be furnished with S-4320 hook latch.
- Pressure lube fittings.
- Blocks furnished with dual rated Wireline sheaves.
- Fatigue Rated.
- All sizes are **RFID EQUIPPED**.
- Meets or exceeds all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, these blocks meet other critical performance requirements including fatigue life and material traceability, not addressed by ASME B30.26.

Fatigue Rated



SEE APPLICATION AND WARNING INFORMATION
On Pages 381-388
Para Español: www.thecrosbygroup.com

420 / 421 / 406 Snatch Blocks

Sheave Diameter (mm)	Bearing Code	Stock No.			Wire Rope Size (mm) †	Working Load Limit (t)*	Weight Each (kg)			Rep. Sheave Stock No.	Rep. Latch Stock No.
		420 with Hook	421 with Shackle	406 Tail Board			420 with Hook	421 with Shackle	406 Tail Board		
152	BB	169374	169481	167973	19-22	12	18.1	21.8	10.9	460940	1096609
152	RB	169392	204120	167982	19-22	12	18.1	21.8	10.9	473035	1096609
203	BB	169418	169515	167991	19-22	15	23.1	25.9	13.6	461360	1096609
203	RB	169445	204193	168008	19-22	15	23.1	25.9	13.6	473534	1096609
254	BB	110221	110720	103186	19-22	15	28.6	31.3	19.1	462001	1096609
254	RB	110258	110757	103202	19-22	15	28.6	31.3	19.1	474025	1096609

* Ultimate Load is 4 times the Working Load Limit. † May be furnished in other rope sizes.



NOTE: When ordering, please specify: size, block number, hook or shackle, bronze bushed or roller bearing, and Wireline size.
NOTE: Tail Board does not contain the spool that is required with the hook (420) and shackle (421) snatch blocks.